

# X-19



## ► FEATURES

- Distinctive aluminum alloy housing for added strength
- Swift 4ms response time
- Crisp 700 contrast ratio
- DVI ready for high quality signal
- S-Video and CVBS inputs
- Auto-adjustment for optimal setting
- Kensington® security socket
- VESA standard wall mount
- Available colors: black, white



## ► SPECIFICATION

Panel	<b>Panel Type</b>	TFT LCD
	<b>Panel Size</b>	19" (483mm)
	<b>Max. Resolution</b>	SXGA 1280 x 1024
	<b>Pixel Pitch</b>	0.294mm
	<b>Brightness</b>	300cd/m <sup>2</sup> (Typical)
	<b>Contrast Ratio</b>	700:1 (Typical)
	<b>Surface Treatments</b>	Hard Coating (3H), Anti-glare Treatment
	<b>Viewing Angle (H/V)</b>	160°/160° (Typical)
	<b>Display Color</b>	16.7M
	<b>Response Time</b>	4ms (GTG)
Input	<b>Frequency (H/V)</b>	H: 30kHz - 80kHz V: 50Hz - 75Hz
	<b>Max. Pixel Clock</b>	135MHz
	<b>Life Time</b>	50,000hrs (Typical)
Connector	<b>Analog</b>	15-Pin D-Sub
	<b>Digital</b>	29-Pin DVI-D
	<b>S-Video</b>	4-Pin Mini Din S-Video
	<b>CVBS</b>	CVBS Jack
NeoV Optical Glass	<b>Power</b>	3-Pin AC Plug
	<b>Thickness</b>	3.0mm (0.18")
	<b>Reflection Rate</b>	<1%
	<b>Transmission Rate</b>	>96%
Tilt	<b>Hardness</b>	>6H (MOH's Rating)
	<b>Tilt</b>	0° ~ +15°
	<b>Mounting</b>	<b>VESA FPMPI</b> Yes (100mm)
Regulation Approval	<b>Certifications &amp; Compliance</b>	FCC, UL/CUL, TUV/GS, CE, BSMI, CB, ISO 13406-2, GOST, WEEE, RoHS
	<b>VESA</b>	DDC 1/2B, DPMS
	<b>Power</b>	<b>Power AC Consumption</b> 100 – 240V, 50 – 60Hz <48W (On) <4W (Stand-by) <2W (Off)
Dimensions	<b>Net (W x H x D)</b>	
	<b>Weight</b>	<b>Net Weight</b> 7.9Kg (17.4lbs)

All specifications are subject to change without prior notice

