



# T1502 Pro

## Technical Data

---

Panel Type	15" TFT active-matrix w/ Touch Screen
Maximum Resolution	1024x768
Display Area	304.1 mm (H) x 228.1 mm (V)
Aspect Ratio	4:3
Contrast ratio	300:1 (typical)
Brightness	250 cd/m <sup>2</sup>
Viewing Angle	160° (H), 160° (V)
Light Source	50,000 hours (typical)
Response Time	25ms (typical)
Touch Sensor	SAW technology
Active Force	2-3 ounces
Life Performance	more than 50 million touches in one location
Glass transmission	more than 90%
Interface	DB9 Serial
Input Signals	RGB Analog (0-750mv, 75Ω) Sync H/V separated (TTL)
Horizontal Frequency	31 – 60 kHz
Vertical Frequency	50-75 Hz
Max. Pixel clock	80 MHz
Color Depth	256k colors/pixel
Connectors	VGA in: 15-pin D-sub Power in: 12 V AC/DC adaptor and 3 pin AC plug Touch Screen: Mini-dim 8 pin connector to DB9 serial
Tilt	0-20 degree
Weight	Gross 16.53 lbs      Net 12.12 lbs
Dimensions	15.19" x 14.17" x 6.65"
Certifications	FCC, UL, CSA, EPA, TUV/GS, CE, DEMKO, SEMKO, NEMKO, FIMKO, TCO 95, NUTEK, BCIQ, VCCI, CCIB
Compliant with Warranty	EPA, NUTEK, VESA DPMS, VESA DDC 1/2B Limited three years

